



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 967 269 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
29.12.1999 Bulletin 1999/52

(51) Int Cl.⁶: C12M 1/33, C12N 1/06

(21) Application number: 99304254.8

(22) Date of filing: 01.06.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Brooks, Robert Cecil
Blewbury, Oxfordshire OX11 9QF (GB)

(74) Representative: Mansfield, Peter Turquand et al
Patents Department,
AEA Technology plc,
329 Harwell
Didcot, Oxfordshire OX11 0RA (GB)


(30) Priority: 13.06.1998 GB 9812713

(71) Applicant: AEA Technology plc
Didcot, Oxfordshire OX11 0RA (GB)

(54) Microbiological cell lysis

(57) Cell lysis may be brought about by contacting a suspension of cells with a lysis reagent such as sodium hydroxide solution; subsequent treatment enables organic molecules such as plasmid DNA to be separated from other cell components. Intimate mixing of the cell suspension with lysis reagent is achieved by passage through a fluidic vortex mixer (18) arranged so the residence time of the cell suspension in the mixer (18)

is less than the time for lysis to be completed, and may be less than 0.1 seconds. Such a vortex mixer (18) comprises a cylindrical chamber with an axial outlet duct and at least one tangential inlet duct, but with no internal baffles. The low shear stress to which the cell suspension is subjected minimizes loss of product through denaturation or fragmentation of the product, and indeed of contaminants. The subsequent treatment may also utilise a fluidic vortex mixer (32).



EP 0 967 269 A1

Description

[0001] This invention relates to a process for treating suspensions of microbiological cells, for example for performing cell lysis, and for treating the fluid produced as a result of cell lysis.

[0002] A range of complex organic molecules can be synthesised within cells, such as bacterial cells, in a fermentation process. The desired product molecules must then be recovered and purified from the cells. In many cases, for example the synthesis of genetic material in the form of plasmid DNA, this is achieved using an initial cell lysis step followed by subsequent processing to remove contaminants through techniques such as precipitation. Cell lysis may be brought about by contacting a suspension of the cells with a lysis reagent such as sodium hydroxide solution. The rate at which homogenous mixing can be achieved is crucial to optimal performance of the lysis reaction. If the rate of mixing is too slow then lysis will occur in discrete regions within the fluids held within the mixer. This will reduce the rate at which lysis agent is able to contact the cells suspended within the fluid, as local increases in viscosity will impede the efficiency of the mixing process. This may result in damage to the desired product as a result of prolonged exposure to shear forces induced by the mixer, and loss of product due to incomplete lysis of the cells, and it increases the possibility of fouling due to the formation of byproducts from the lysis reagent cross reacting with other cell components released subsequent to lysis.

[0003] According to the present invention there is provided a method for processing cells wherein an aqueous suspension of cells is intimately mixed with a lysis reagent by passage through a fluidic vortex mixer, the dimensions of the mixer and the flow rates being such that the residence time of the cell suspension in the mixer is less than the time for lysis to be completed.

[0004] A fluidic vortex mixer comprises a substantially cylindrical chamber with an axial outlet duct at the centre of an end wall of the chamber, and with at least one substantially tangential inlet near the periphery of the chamber to create a spiralling flow in the chamber. A second liquid may be supplied through a second tangential inlet, or through a radial inlet. The chamber contains no vanes or baffles. Such a mixer achieves a very intimate mixing of the two liquids in a very short time, yet it does not subject the liquids to high shear. It is also much less prone to being fouled, for example by proteinaceous deposits, than other types of mixer.

[0005] The residence time means the time taken by the cell suspension to pass through the mixer. This is preferably much less than the time taken for lysis to be completed, and is preferably less than 0.1 seconds, more preferably less than 0.01 seconds, so that the emerging liquid mixture is of viscosity similar to that of the in-flowing cell suspension. In this specification 'completion of lysis' refers to both the breaking down of the

cell walls and the resulting increase in viscosity as cellular proteins and chromosomal DNA released from the cells interact with the lysis reagent. Preferably the viscosity increases during passage through this mixer by a factor of no more than ten times, more preferably no more than five times, for example less than twice. The low shear stress to which the cell suspension is subjected minimizes loss of product through denaturation or fragmentation of the product, and indeed of contaminants. Furthermore the rapid, intimate mixing ensures that all the cells are subjected to optimal conditions for lysis to occur.

[0006] The cell processing procedure usually involves subsequent treatment of the lysed cells with a precipitation agent. The invention also envisages a mixture of cell suspension and lysis reagent being mixed with the precipitation agent by passage through a fluidic vortex mixer. This may be a second such vortex mixer. Alternatively the precipitation agent may be mixed with the mixture of cell suspension and lysis reagent during its passage through the first vortex mixer, by supplying the precipitation agent to a third inlet duct into the first vortex mixer; this third inlet duct preferably communicates with the outlet duct from the chamber, and the open end of this third inlet duct may be adjustable in its position along the axis of the outlet duct.

[0007] The invention will now be further and more particularly described by way of example only, and with reference to the accompanying drawing which shows a flow diagram for a cell product recovery system.

[0008] Referring to the drawing, a system 10 is shown for obtaining plasmid DNA. Bacteria (*Escherichia coli*) genetically engineered to make the desired plasmid DNA are grown in a fermentation vessel 12. When sufficient fermentation has taken place, an aqueous cell suspension is pumped from the vessel 12 by a low-shear pump 16 (such as a mono pump) to one tangential inlet of a fluidic vortex mixer 18. An aqueous solution of sodium hydroxide is supplied from a storage tank 20 via a pump 22 to a second tangential inlet of the vortex mixer 18. The resulting intimate mixture of cell suspension and sodium hydroxide emerges from an axial outlet 24 of the mixer 18; the residence time of the cell suspension in the mixer 18 is less than 0.1 seconds.

[0009] By way of exemplification, the flow rate through the mixer 18 might be one litre per minute, and the cylindrical chamber in the mixer 18 might be of diameter 10 mm and of height 2 mm, the two inlet ducts being of cross-sectional area 1 mm² and the outlet duct 24 of diameter 2 mm. This would provide a residence time of about 8 ms. If the flow rate through this mixer 18 were halved, to 0.5 litre/min, the mean residence time would be doubled, to about 16 ms.

[0010] The mixture from the outlet 24 is supplied to a tank 26, in which lysis is completed. The cell membranes break down, and open-strand DNA and RNA form complexes with each other and with proteins; consequently the mixture uniformly increases in viscosity.

The tank has an outlet duct 28 at the bottom, the flow rates and the dimensions of the tank 26 being such that the residence time of the mixture in the tank 26 is sufficient to ensure lysis is complete, for example one minute, or 10 minutes. Mixture from the tank 26 is pumped by a low-shear pump 30 such as a mono pump to a tangential inlet of a second fluidic vortex mixer 32; a buffer solution of sodium acetate and acetic acid is pumped from a storage tank 34 by a pump 36 to another tangential inlet of the fluidic vortex mixer 32, and the resulting mixture is supplied to a tank 40. The buffer solution lowers the pH of the mixture to about pH 3.5, and the complexes consequently precipitate. As with the mixer 18, the mixing process in the mixer 32 takes place rapidly, and the residence time is less than the induction time for precipitation to commence so that there is no tendency for fouling due to proteinaceous deposits in the mixer 32.

[0011] The mixture from the tank 40 is then supplied to a centrifuge 42, such as a disk stack centrifuge, to separate the precipitate (which contains proteins and precipitated open-strand chromosomal DNA and host-cell RNA) from the supernatant liquid (which contains the plasmid DNA).


[0012] It will be appreciated that the system 10 can be modified in various ways while remaining within the scope of the present invention. For example, the cells from the cell fermentation tank 12 might be separated from the aqueous fermentation medium by centrifuging, and then resuspended in an appropriate aqueous solution, before being supplied to the fluidic vortex mixer 18. Alternatively, in the system 10, the pump 16 might be omitted and the cell suspension supplied directly to the vortex mixer 18 as a result of gas pressure or hydrostatic pressure in the tank 12. The tank 26 in which lysis is completed may be provided with an impeller, and indeed may be subdivided axially into successive cells with a common impeller, to provide better control over the residence time. In a further alternative, the buffer solution from the tank 34 (which causes precipitation) might instead be supplied through a capillary tube (not shown) into the outlet duct 24 so as to feed the buffer solution directly into the swirling liquid near the axis of the duct 24; the duct 24 can then be connected directly to the precipitation tank 40. This enables the cell walls to be broken down, but prevents the subsequent unravelling of the cell contents and the consequential increase in viscosity from occurring.

chamber, and with at least two inlets at or near the periphery of the chamber, at least one inlet being substantially tangential so as to cause spiralling flow in the chamber, the chamber containing no baffles, and the dimensions of the mixer and the flow rates being such that the residence time of the cell suspension in the mixer is less than the time for lysis to be completed.

2. A method as claimed in claim 1 wherein the residence time is sufficiently short that the viscosity of the mixture increases by a factor of less than two during passage through the fluidic vortex mixer (18).
3. A method as claimed in claim 1 or claim 2 wherein the residence time is less than 0.01 seconds.
4. A method as claimed in any one of the preceding claims wherein the mixture of cell suspension and lysis reagent is subsequently mixed with a precipitation agent (34) by passage through a second fluidic vortex mixer (32).
5. A method as claimed in any one of claims 1 to 3 wherein a precipitation agent is injected into the mixture of cell suspension and lysis reagent within the outlet (24) from the fluidic vortex mixer (18).

Claims

1. A method for processing cells wherein an aqueous suspension of cells is intimately mixed with a lysis reagent by passage through a mixer, characterised by the mixer being a fluidic vortex mixer (18) comprising a substantially cylindrical chamber with an axial outlet (24) at the centre of an end wall of the





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 4254

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
Y	US 4 775 622 A (HITZEMAN RONALD A ET AL) 4 October 1988 (1988-10-04) * column 6, line 40 - line 65; claims *	1,4	C12M1/33 C12N1/06
Y	EP 0 271 667 A (PHILLIPS PETROLEUM CO) 22 June 1988 (1988-06-22) * claims; example 1 *	1,4	
Y	US 5 047 345 A (DEBONVILLE DAVID A ET AL) 10 September 1991 (1991-09-10) * claims; example 2 *	1,4	
A	US 5 437 985 A (QUINTANA JORGE A ET AL) 1 August 1995 (1995-08-01)		
A	US 4 880 746 A (WOHLLEBEN WOLFGANG ET AL) 14 November 1989 (1989-11-14)		
A	WO 96 12956 A (WATSON CLINIC FOUNDATION) 2 May 1996 (1996-05-02)		
A	FR 1 576 299 A (VYZKUMNY USTAV ORGANICKYCH SYTEZ PARDUBICE RYBITVI) 25 July 1969 (1969-07-25)		
A	EP 0 341 215 A (CIBA GEIGY AG ;UCP GEN PHARMA AG (CH)) 8 November 1989 (1989-11-08)		
A	WO 91 01367 A (BIOENG INC) 7 February 1991 (1991-02-07)		
A	EP 0 626 456 A (BECTON DICKINSON CO) 30 November 1994 (1994-11-30)		
A	US 4 652 517 A (SCHOLL DAVID R ET AL) 24 March 1987 (1987-03-24)		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 18 October 1999	Examiner Coucke, A
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1500 (01-92) (P.02/01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 4254

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-10-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4775622 A	04-10-1988	AT 90728 T	15-07-1993
		AU 574323 B	07-07-1988
		AU 1215283 A	15-09-1983
		BG 46159 A	16-10-1989
		BR 8301150 A	22-11-1983
		CZ 8301608 A	16-07-1997
		DD 207220 A	22-02-1984
		DE 3308215 A	17-11-1983
		DE 3382694 A	22-07-1993
		DK 111283 A,B,	28-10-1983
		EP 0088632 A	14-09-1983
		ES 520416 A	01-11-1984
		FI 830774 A	09-09-1983
		FR 2523152 A	16-09-1983
		GB 2116567 A,B	28-09-1983
		GR 78506 A	27-09-1984
		IE 55743 B	02-01-1991
		JP 8029111 B	27-03-1996
		JP 58174396 A	13-10-1983
		JP 6181779 A	05-07-1994
		NZ 203494 A	11-06-1986
		OA 7338 A	31-08-1984
		PH 24804 A	30-10-1990
		PT 76360 A,B	01-04-1983
		RO 88582 A	28-02-1986
		YU 55683 A	31-08-1989
		ZW 6283 A	01-06-1983
		ZA 8301569 A	25-04-1984
EP 0271667 A	22-06-1988	US 4683293 A	28-07-1987
		AU 586758 B	20-07-1989
		AU 7717887 A	21-04-1988
		CA 1277272 A	04-12-1990
		CN 1006808 B	14-02-1990
		CS 8707529 A	13-08-1991
		DD 262673 A	07-12-1988
		DK 545187 A	21-04-1988
		FI 874597 A	21-04-1988
		IN 166069 A	10-03-1990
		JP 63105693 A	10-05-1988
		NZ 221296 A	27-07-1989
		PH 23461 A	07-08-1989
		PT 85935 A,B	01-11-1987
		YU 191387 A	30-06-1989
US 5047345 A	10-09-1991	AU 635207 B	18-03-1993

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 4254

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-10-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5047345 A		CA 1328839 A	26-04-1994
		WO 9014416 A	29-11-1990
		AU 3696189 A	18-12-1990
		DE 68914689 D	19-05-1994
		DE 68914689 T	27-10-1994
		EP 0473575 A	11-03-1992
		AT 104338 T	15-04-1994
US 5437985 A	01-08-1995	US 5030554 A	09-07-1991
		AU 606493 B	07-02-1991
		AU 2820489 A	05-07-1989
		CA 1319592 A	29-06-1993
		DE 3854326 D	21-09-1995
		DE 3854326 T	04-04-1996
		EP 0344287 A	06-12-1989
		JP 7026955 B	29-03-1995
		JP 2502487 T	09-08-1990
		WO 8905092 A	15-06-1989
US 4880746 A	14-11-1989	DE 3412092 A	14-11-1985
		DE 3412093 A	10-10-1985
		AT 40153 T	15-02-1989
		AU 582149 B	16-03-1989
		AU 4059985 A	03-10-1985
		CA 1246475 A	13-12-1988
		DK 145185 A	01-10-1985
		EP 0158872 A	23-10-1985
		ES 541716 A	16-12-1985
		GR 850797 A	25-11-1985
		JP 2526203 B	21-08-1996
		JP 60256384 A	18-12-1985
		PT 80188 A, B	01-04-1985
		AT 55152 T	15-08-1990
		AU 4060085 A	03-10-1985
		CA 1246474 A	13-12-1988
		DK 144985 A	01-10-1985
		EP 0158201 A	16-10-1985
		ES 541718 A	16-12-1985
		GR 850798 A	23-07-1985
		JP 2619855 B	11-06-1997
		JP 60217895 A	31-10-1985
		PT 80189 A, B	01-04-1985
		US 4992371 A	12-02-1991
WO 9612956 A	02-05-1996	AU 689346 B	26-03-1998
		AU 4016895 A	15-05-1996

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 4254

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-10-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9612956	A		BR 9507579 A	09-09-1997
			CA 2184826 A	02-05-1996
			EP 0725933 A	14-08-1996
			FI 963848 A	26-09-1996
			JP 10512951 T	08-12-1998
			NO 963780 A	25-08-1997
FR 1576299	A	25-07-1969	NL 6811627 A	20-02-1969
EP 0341215	A	08-11-1989	AT 124086 T	15-07-1995
			AU 614121 B	22-08-1991
			AU 3382889 A	09-11-1989
			CA 1340016 A	25-08-1998
			DD 283839 A	24-10-1990
			DE 68923123 D	27-07-1995
			DE 68923123 T	30-11-1995
			DK 217589 A	05-11-1989
			ES 2072918 T	01-08-1995
			FI 892114 A	05-11-1989
			IE 66044 B	13-12-1995
			IL 90170 A	31-12-1995
			JP 2104279 A	17-04-1990
			JP 2107291 C	06-11-1996
			JP 8024565 B	13-03-1996
			KR 9705584 B	18-04-1997
			MX 169508 B	08-07-1993
			NO 180593 B	03-02-1997
			NZ 228955 A	25-06-1991
			PT 90436 A, B	30-11-1989
WO 9101367	A	07-02-1991	US 5380826 A	10-01-1995
EP 0626456	A	30-11-1994	CA 2121659 A	12-11-1994
			JP 2575290 B	22-01-1997
			JP 6319598 A	22-11-1994
			SG 44811 A	19-12-1997
			US 5554503 A	10-09-1996
US 4652517	A	24-03-1987	AT 79474 T	15-08-1992
			AU 594925 B	22-03-1990
			AU 4431385 A	10-01-1986
			DE 3586490 A	17-09-1992
			EP 0188450 A	30-07-1986
			JP 4030279 B	21-05-1992
			JP 61502376 T	23-10-1986
			WO 8600139 A	03-01-1986

EPO FORM P4459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82